

Innovations

and Spring-Summer Campaign 2021






Our Spring 2021 product innovations

NEM

Kraftform Kompakt Stubby magazine 1



Application: Suitable for bits with $^{1}\!/_{4}$ " external hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1


Design: Bit holder with strong permanent magnet; BiTorsion bits for long service life, tough, for universal use. Take it easy tool finder: Size stamping and tips with colour coding to find the required bit quickly.

Handle: Kraftform Stubby with anti-roll protection, multi-component, integrated magazine

•		
05 008873 001		
0	851/1 BTZ PH	1x PH 1x25; 1x PH 2x25
0	867/1 TORX® BTZ	1x TX 15x25; 1x TX 20x25; 1x TX 25x25
•	800/1 BTZ	1x 0,8x5,5x25

M = M

Kraftform Kompakt Stubby magazine 2



Design:Bit holder with strong permanent magnet; BiTorsion bits for long service life, tough, for universal use. Take it easy tool finder: Size stamping and tips with colour coding to find the required bit quickly.

Handle: Kraftform Stubby with anti-roll protection, multi-component, integrated magazine

•		
05 008874 001		
•	800/1 BTZ	1x 0,8x5,5x25; 1x 1,2x6,5x25
•	851/1 BTZ PH	1x PH 1x25; 1x PH 2x25
0	855/1 BTZ PZ	1x PZ 1x25; 1x PZ 2x25

Kraftform Kompakt Stubby magazine 3



Application: Suitable for bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1

Bit holder with strong permanent magnet; BiTorsion bits for Design:

long service life, tough, for universal use. Take it easy tool finder: Size stamping and tips with colour coding to find the required bit quickly.

Handle: Kraftform Stubby with anti-roll protection, multi-component,

integrated magazine

05 008875 001		
0	867/1 TORX® BTZ	1x TX 15x25; 1x TX 20x25; 1x TX 25x25
0	840/1 BTZ Hex-Plus	1x 3,0x25; 1x 4,0x25; 1x 5,0x25

Kraftform Kompakt Stubby magazine 5



Application: Suitable for bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1

Bit holder with strong permanent magnet; bits, tough, for Design:

Handle: Kraftform Stubby with anti-roll protection, multi-component,

integrated magazine

-		
05 008878 001		
0	851/1 Z PH	1x PH 1x25; 1x PH 2x25
•	800/1 Z	1x 1.0x5.5x25; 1x 1.2x6.5x25
0	868/1 Z	1x # 1x25; 1x # 2x25

Kraftform Kompakt Stubby magazine 4



Application: Suitable for bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1

Design: Bit holder with strong permanent magnet; bits, tough, for

Handle: Kraftform Stubby with anti-roll protection, multi-component,

integrated magazine

05 008877 001		
0	851/1 Z PH	1x PH 1x25; 1x PH 2x25; 1x PH 3x25
•	800/1 Z	1x 0.6x4.5x25; 1x 1.0x5.5x25; 1x 1.2x6.5x25

Handle with integrated bit magazine



The handle can be opened and thus gives access to the six bits contained in the magazine.

Compact shape



With its compact handle shape and the short blade, the Kraftform Stubbies are particularly suitable for working in confined screwdriving situations.

Swiveling bit magazine



The swiveling bit magazine allows for the bits to be removed easily in almost any situation and cannot be lost. The bits are safely stored.

Joker 6004 self-setting, adjustable spanner Self-setting. Gripping. Ratcheting.



Automatically and continuously self-setting



With its automatically and continuously gripping parallel jaws the Joker spanner 6004 covers all dimensions in the respective field of application. The tool automatically finds the required size when placed on the bolt or screw, no setting required.



Gentle to the screw



The parallel smooth jaws of the Joker 6004 allow surface pressure and can thus prevent rounding of the bolt or screw head, which can occur during power transmission on corners.



Ratchet mechanism for fast work



The ratchet function in the mouth sees to fast and consistent screwdriving without removing the tool.



6004 Joker XL self-setting spanner









Application: Hexagon screw heads and bolts with wrench size 19-24 (metric) or $^3/_4$ "- $^{15}/_{16}$ " (imperial)

Design: Self-setting spanner with ratchet function; size-adjustable mouth side, parallel smooth jaws; with 30° return angle due to the corner-width rectangular prisms in the mouth; hole for

•						
		\bigcirc	Ĩ,	1		
	mm		mm	mm		
05 020104 001	19-24	3/4"-15/16"	256	16		



Joker 6003 ring spanner Mouth side with only 15° back-pivoting angle. When things get tight.



6003 Joker combination wrench





Application: Hexagon screw heads and bolts

Design: Combination wrench; open-end offset by 7,5°, ring side pivoted by 15°; with Take it easy tool finder: colour coding by size

•						
	(4)	ľ,	\ <u>\</u>	1	0	
	mm	mm	mm	mm	mm	
05 020190 001 ¹⁾	5,5	105	16	4	10	
05 020198 001 ¹⁾	6	105	16	4	10	
05 020199 001 ¹⁾	7	110	17,7	4,2	11,5	
05 020219 001 ¹⁾	9	120	21	4,8	13,5	
05 020500 001 ¹⁾	20	230	45	7,5	29	
05 020501 001 ¹⁾	21	260	47	7,5	30	
05 020502 001 ¹⁾	22	260	49	7,5	31,5	
05 020503 001 ¹⁾	24	280	53	8	36	
05 020504 001 ¹⁾	27	300	60	8,5	40	
05 020505 001 ¹⁾	30	330	66	9	43	
05 020506 001 ¹⁾	32	360	70	9,5	45,5	
05 020507 001 ¹⁾	36	460	80	10	50,5	

¹⁾Available from May 2021

NEW

6003 Joker combination wrench, Imperial





Application: Hexagon screw heads and bolts

Design: Combination wrench; open-end offset by 7,5°, ring side pivoted by 15°; with Take it easy tool finder: colour coding by size

•						
	$\langle \Box \rangle$	Ĩ,	Ÿ	1	0	
		mm	mm	mm	mm	
05 020220 001 ¹⁾	1/4"	105	16	4	10	

1) Available from May 2021







MEW


Patio construction set T 1











Compact Wera tool set with the 17 most common screwdriving tools for patio construction. 1 bit holder with variable screw depth limitation, with retaining ring for a secure hold of the bits, 4 spare felt rings, which prevent brush marks on the patio decking, 1 Rapidaptor Stainless bit holder with quick-release chuck, 15 Stainless bits in stainless steel design to prevent extraneous rust, Take it easy tool finder: Colour coding in accordance to profile & size stamp, helps find the required bit quickly.

+		
05 134021 001		
●0	881/4/1	1x ¹ / ₄ "x90 ¹⁾
●0	3888/4/1 K	1x ¹ / ₄ "x50
•	3851/1 TS PH	1x PH 1x25; 1x PH 2x25; 1x PH 3x25
•	3855/1 TS PZ	1x PZ 1x25; 2x PZ 2x25; 1x PZ 3x25
0	3867/1 TS	1x TX 10x25; 1x TX 15x25; 1x TX 20x25;
	TORX®	1x TX 25x25; 1x TX 30x25; 1x TX 40x25
0	3867/1 TS P TORX®	2x TX 25x25
	9201	4x 27,0

The spare part kit with 5x felt rings can be ordered with the code number 05130003001

NEW

881/4/1 SB Bit holder with variable screw depth limitation



Tip: Suitable for mounting bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1

Design: With adjustable screw depth limitation; allows the flush countersinking of screws; the felt ring (exchangeable) in the front of the bit mounting prevents brush marks on the patio decking; the retaining ring holds the bit securely in the holder

Drive: 1/4" hexagon, suitable for power screwdrivers with mounting as per DIN ISO 1173-F 6.3

•		
05 130002 001		
●0	881/4/1	1x ¹ / ₄ "x90 ¹⁾
	9201	2x 27,0

¹⁾The spare part kit with 5x felt rings can be ordered with the code number 05**130003**001.



Evenly flush countersinking of screws



The 881/4/1 bit holder allows for evenly flush countersinking of screws in decking when building patios. The screw depth can be adjusted as required. This prevents screws from being countersunk too deep.

Avoids damage caused by rot



The screw head is evenly flush with the decking, therefore so-called "water nests", which usually lead to rot, are avoided.

Individual screw depth



The required screw depth is set using the counter thread.

Bit mounting with retaining ring



Proven holder design, optimal fitting of the tool in the holder. Particularly robust for series applications.

Click-Torque R/L





Click-Torque R/L: For right and left direction



The Click-Torque torque wrench R/L is suitable for clockwise and anti-clockwise torque-control. Very smooth change of direction thanks to captive square head insert.



Exact



Precise to \pm 3% as per DIN EN ISO 6789-1:2017-07.



Simple setting



With audible and tactile clicks when adjusting the scale values.

Simple and safe



Easy setting and saving of the desired torque value; readable on the main and fine scales.

Click-Torque C 2 Push R/L adjustable torque wrench for clockwise and anti-clockwise torque-control, 20-100 Nm



Application: For clockwise and anti-clockwise torque-control

Precision: Precise to ±3 % of the set value, as per DIN EN ISO 6789-1:2017-07

Design: With \(^1/2\)^2 square head drive with socket locking, square head insert to change the tightening direction, fine-teethed ratchet mechanics, 45 teeth; easy setting and saving of the desired torque, with audible and tactile locking when the scale values are reached (fine scale only in Newton

meters), audible and tactile release mechanism when the torque value is reached

Handle: Ergonomic 2-component handle

•														
	0	 	╢┉╢	 	₫= ===	o====	•		† □-	ئىست	œ =	0=		♦ □
		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05 075625 001 ¹⁾	1/2"	20-100	0,5	15-73	405	140	47	43	18,5	15 ¹⁵ /16"	5 33/64"	1 27/32"	1 11/16"	⁴⁵ / ₆₄ "

¹⁾ Available from May 2021

MEW

Click-Torque C 3 Push R/L adjustable torque wrench for clockwise and anti-clockwise torque-control, 40-200 Nm



Application: For clockwise and anti-clockwise torque-control


Precision: Precise to $\pm 3\%$ of the set value, as per DIN EN ISO 6789-1:2017-07

Design: With ½" square head drive with socket locking, square head insert to change the tightening direction, fine-teethed ratchet mechanics, 45 teeth;

easy setting and saving of the desired torque, with audible and tactile locking when the scale values are reached (fine scale only in Newton

meters), audible and tactile release mechanism when the torque value is reached

Handle: Ergonomic 2-component handle



¹⁾Available from May 2021

M = M

Click-Torque E 1 Push R/L adjustable torque wrench for clockwise and anti-clockwise torque-control, 200-1000 Nm



Application: For clockwise and anti-clockwise torque-control

Precision: Precise to ±3 % of the set value, as per DIN EN ISO 6789-1:2017-07

Design: With ³/₄" square head drive, square head insert to change the tightening direction, fine-teethed ratchet mechanics, 45 teeth; easy setting and saving of the desired torque, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and

tactile release mechanism when the torque value is reached

Handle: Ergonomic 2-component handle

	0		 <u> </u> 		أ⊫	م	0=		1	ئ ے	•=====================================	0=		♦
		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05 075631 001 1)	3/4"	200-1000	1,0	148-737	1250	140	47	63	30	49 7/32"	5 33/64"	1 27/32"	2 31/64"	1 3/16"

For mobile phones, tablets and laptops/ desktops.

- ESD-safe tool thanks to surface resistance of ≤ 10⁹ ohm
- The fast-turning zone just below the rotating cap allows rapid twisting
- The Wera Black Point tip offers an exact fit and optimum corrosion protection
- Multi-component Kraftform Micro handles for fast and ergonomic screwdriving
- Included profiles especially suitable for servicing mobile phones, tablets and laptops/desktops
- Take it easy tool finder: colour coding according to profile and size
- Storage and transport in a robust textile bag, so the tool is well protected and always close



Kraftform Micro ESD Big Pack 1 screwdriver set for




















Application: Slotted screws, Phillips-Recess screws, TORX® socked screws (TX 8, TX 10 with holding function), TORX PLUS® IPR socket screws, Pentalobe screws, external hexagon bolts and Microstix® screws. One lifting fork for removing stuck components on printed circuit boards after unsoldering

Design: 25-piece set; in folding bag

•		
05 134019 001		
0	1550 PH ESD	1x PH 000x40 ^{1) 2)} ; 1x PH 00x40 ^{1) 2)} ;
	Micro	1x PH 0x40 ³⁾ ; 1x PH 1x80
0	1550 PH S	1x # 01x40
	ESD Micro	
0	1567 TORX®	1x TX 8x60; 1x TX 10x60
	HF ESD Micro	
0	1567 TORX®	1x TX 2x40; 1x TX 3x40; 1x TX 4x40;
	ESD Micro	1x TX 5x40; 1x TX 6x40
•	1567 TORX®	1x TX 6 B0x60; 1x TX 8 B0x60
	BO ESD Micro	
0	1567 TORX	1x 1 IPRx40
	PLUS® IPR	
	ESD	
٥	1572 ESD	1x mx40; 1x 00x40; 1x Fx40; 1x 0x40
0	1573	1x PL 1,1x40; 1x PL 1,4x40
	Pentalobe	2 .,
	ESD	
•	1569 ESD	1x 3,0x60
		·
•	1578 A ESD	1x 0,16x0,8x40; 1x 0,23x1,5x40
	Micro	
•	1529 ESD	1x 1,0x3,5x50

³⁾Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)



²⁾ On the output side, the blade is turned to a nominal length of 10 mm.

Kraftform Micro 6 ESD smartphone repair kit 1





With Take it easy Tool Finder: colour coding by profile and size stamping

Application: Phillips-Recess, TORX PLUS® IPR and Microstix® screws, 1

lifting fork for removing stuck components on printed circuit boards after unsoldering

Design: 6-piece set in a cardboard box + rack


+		
05 030182 001		
0	1550 PH ESD Micro	1x PH 00x40 1) 2); 1x PH 0x40 3)
0	1567 TORX PLUS® IPR ESD	1x 1 IPRx40
٥	1572 ESD	1x mx40
0	1550 PH S ESD Micro	1x # 01x40
•	1529 ESD	1x 1,0x3,5x50

¹⁾ Optimised for Asian PH screws

NFW

950/9 Hex-Plus Multicolour Imperial 2 L-key set, Imperial, BlackLaser





9-piece set in a two-component clip

Application: Hexagon socket screws


Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy

to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

•	
05 022640 001	
0	950 SPKL inch 1x ⁵ / ₆₄ "x101; 1x ³ / ₃₂ "x112; 1x ¹ / ₈ "x123; 1x ⁵ / ₃₂ "x137; 1x ³ / ₁₆ "x154; 1x ⁷ / ₃₂ "x172; 1x ¹ / ₄ "x185; 1x ⁵ / ₁₆ "x195; 1x ³ / ₈ "x224

Kraftform Micro 6 ESD smartphone repair kit 1: For mobile phones and tablets



The screwdriver profiles included in this set are especially suitable for servicing mobile phones and tablets.



High protection



The electric surface resistance of the Wera ESD material is $\leq 10^9$ ohm. This securely protects components against electrostatic energy and associated damage.



Take it easy Tool Finder



Screwdrivers with Take it easy tool finder: colour coding according to profile and size stamp.



Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that

prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

 $^{^{2)}\}mbox{On the output side, the blade is turned to a nominal length of 10 mm.$

 $[\]ensuremath{^{\scriptscriptstyle{3)}}}\textsc{Size}\ 0$ modificated according to JCIS 0 (Japanese Camera Industrial Standard)



Limited Editions – when they're gone, they're gone



MEW

Kraftform/7 Heavy Metal 1















With Take it easy Tool Finder: colour coding by profile and size stamping.

Application: Slotted screws, Phillips-Recess and TORX®, with holding function for TORX® screws as per the Acument Intellectual Properties specification

Design: 7-piece set in a cardboard box + rack + Tool Rebel bottle opener

•		
05 138711 001		
0	350 PH	1x PH 1x80; 1x PH 2x100
0	367 TORX® HF	1x TX 20x100; 1x TX 25x100
•	335	1x 0,8x4,0x100; 1x 1,0x5,5x125
•	160 iS	1x 0,6x3,5x100
	Bottle opener Tool Rebel	1x 35x50



Take it easy Tool Finder



Screwdrivers with Take it easy tool finder: colour coding according to profile and size stamp.

Bottle opener Tool Rebel



A full-metal bottle opener, which is also usable as a key ring.

NEW

Kraftform VDE/7 Heavy Metal 2













Kraftform: The safety screwdriver. Includes some tools with reduced blade diameter. With Take it easy Tool Finder: colour coding by profile and size stamping.

Application: Slotted screws, Phillips-Recess, combination profile Pozidriv/slotted and TORX® screws

Design: 7-piece set in a cardboard box + rack + Tool Rebel bottle opener

•		
05 138712 001		
0	162 iS	1x PH 1x80; 1x PH 2x100
0	165 iS PZ/S	1x # 2x100
•	160 iS	1x 0,6x3,5x100; 1x 1,0x5,5x125
0	167 i TORX® VDE	1x TX 20x80; 1x TX 25x100
	Bottle opener Tool Rebel	1x 35x50

NEW

Kraftform VDE/7 Heavy Metal 3

















Limited Editions – when they're gone, they're gone. With Take it easy Tool Finder: colour coding by profile and size stamping.

Application: Slotted and Phillips-head screws, Phillips-head screws
Phillips-Recess, square head socket screws and combination
profile Phillips/slotted

Design: 7-piece set in a cardboard box + rack + Tool Rebel bottle

+		
05 138710 001		
•	932 A	1x 1.0x5.5x100; 1x 1.2x7.0x125
0	350 PH	1x PH 1x80; 1x PH 2x100
0	368	1x # 2x100
0	162 iS PH/S	1x # 2x100
•	160 iS	1x 0.6x3.5x100
	Bottle opener Tool Rebel	1x 35x50





Wera Tools Inc. (North America) 3325 Harvester Rd, Unit 16 Burlington, Ontario Canada, L7N 3N2

Phone: 1-800-267-55 41 E-Mail: info@weratools.com www.weratools.com